



061.25.1250.101.21.1504 Rothe erde slewing bearing

Bearing No. 6017

6017 Bearing 2D drawings and 3D CAD models

Size	130x85x22 mm
Bore Diameter	130 mm
Outer Diameter	85 mm
Width	22 mm
d	85 mm
D	130 mm
B	22 mm
d <sub>1</sub>	99.4 mm
D <sub>2</sub>	119.1 mm
r <sub>1,2</sub> - min.	1.1 mm
d <sub>a</sub> - min.	92 mm
D <sub>a</sub> - max.	123 mm
r <sub>a</sub> - max.	1 mm
Basic dynamic load rating - C	52 kN
Basic static load rating - C <sub>0</sub>	43 kN
Fatigue load limit - P <sub>u</sub>	1.8 kN
Reference speed	11000 r/min
Limiting speed	6700 r/min
Calculation factor - k <sub>r</sub>	0.025
Calculation factor - f <sub>0</sub>	15.8
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A



Weight / Kilogram	0.941
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	85MM Bore; 130MM Outside Diameter; 22MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	6017
Weight / LBS	2.07
Outside Diameter	5.118 Inch   130 Millimeter
Bore	3.346 Inch   85 Millimeter
Outer Race Width	0.866 Inch   22 Millimeter
d <sub>1</sub>	99.4 mm
D <sub>2</sub>	119.1 mm
r <sub>1,2</sub> min.	1.1 mm
d <sub>a</sub> min.	92 mm



D <sub>a</sub> max.	123 mm
r <sub>a</sub> max.	1 mm
Basic dynamic load rating C	52 kN
Basic static load rating C <sub>0</sub>	43 kN
Fatigue load limit P <sub>u</sub>	1.76 kN
Calculation factor k <sub>r</sub>	0.025
Calculation factor f <sub>0</sub>	15.8
Mass bearing	0.9 kg