



062.30.1400.001.21.1504 thyssenkrupp rothe erde slewing bearing

Bearing No. 6202

6202 Bearing 2D drawings and 3D CAD models

Size	15x35x11 mm
Bore Diameter	15 mm
Outer Diameter	35 mm
Width	11 mm
d	15 mm
D	35 mm
B	11 mm
C	11 mm
r min.	0,6 mm
da min.	19 mm
da max	20,5 mm
Da max.	31 mm
ra max.	0,6 mm
Weight	0,045 Kg
Basic dynamic load rating (C)	7,65 kN
Basic static load rating (C0)	3,75 kN
(Grease) Lubrication Speed	20 000 r/min
(Oil) Lubrication Speed	24 000 r/min
Category	Single Row Ball Bearings
Inventory	2.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.047
EAN	0029176013867
Product Group	B00308



Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nskamericas.com
Manufacturer Item Number	6202
Weight / LBS	0.1
Bore	0.591 Inch 15 Millimeter
Outer Race Width	0.433 Inch 11 Millimeter
Outside Diameter	1.378 Inch 35 Millimeter
SRI	3.01
hidYobi	6202
LangID	1
D_	35
SREX	0.03
B_	11



da min	19
hidTable	ecat_NSRDGB
Oil rpm	24000
SRE	3.16
mass	0.045
GRS rpm	20000
ra	0.6
SRIX	0.015
D_a	31
SRIN	0
C0	3.75
fo	13.2
SREN	0
DE_	31.453
Prod_Type3	DGBB_SR_OT
DA_	5.953
bomp	0
Z_	8
yobi	6202
C_conv	7650
ALPHA_	0
SDM_	25.5
r	0.6
KBRG	6101
SBRG	2
DI_	19.547