



61814 Bearing 2D drawings and 3D CAD models

162.25.1320.890.11.1503 slewing rings without gear

Bearing No. 61814

Size	90x70x10 mm
Bore Diameter	90 mm
Outer Diameter	70 mm
Width	10 mm
d	70 mm
D	90 mm
B	10 mm
d ₁	76.6 mm
D ₁	83.4 mm
r _{1,2} - min.	0.6 mm
d _a - min.	73.2 mm
D _a - max.	86.8 mm
r _a - max.	0.6 mm
Basic dynamic load rating - C	12.4 kN
Basic static load rating - C ₀	13.2 kN
Fatigue load limit - P _u	0.56 kN
Reference speed	15000 r/min
Limiting speed	9000 r/min
Calculation factor - k _r	0.015
Calculation factor - f ₀	17.2
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A



Weight / Kilogram	0.154
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	70MM Bore; 90MM Outside Diameter; 10MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	61814
Weight / LBS	0.34
Bore	2.756 Inch 70 Millimeter
Outer Race Width	0.394 Inch 10 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
bore diameter:	70 mm
static load capacity:	13.2 kN
outside diameter:	90 mm
precision rating:	Not Rated



overall width:	10 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	10 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.6 mm
snap ring included:	Without Snap Ring
maximum rpm:	9000 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	12.4 kN
d_1	76.4 mm
D_1	83.9 mm
$r_{1,2}$ min.	0.6 mm
d_a min.	73.2 mm
D_a max.	86.8 mm
r_a max.	0.6 mm
Basic dynamic load rating C	12.4 kN
Basic static load rating C_0	13.2 kN
Fatigue load limit P_u	0.56 kN
Calculation factor k_r	0.015
Calculation factor f_0	17.2
Mass bearing	0.14 kg